

2 Monitor Professional High Performance Remote Monitoring Workstation

The innovative Avigilon[™] hardware solutions portfolio provides a secure, reliable, and scalable platform from small sites and large systems. Our high-performance HD remote monitoring workstation enables you to add to an existing Avigilon system for superior monitoring and protection.



The professional high performance remote monitoring workstations are designed to achieve the highest performance for a client workstation within an Avigilon HD Surveillance System. Pre-loaded with Avigilon Control Center[™] Client software, the remote monitoring workstation is easily installed to accompany NVR products and to add an additional monitoring station to existing systems, with support for two high resolution monitors* and up to a total of 72 video streams.

KEY FEATURES

Preloaded with Avigilon Control Center High Definition Network Video Management Client Software

Supports up to two high resolution monitors*

Supports viewing up to 72 video streams simultaneously

Desktop form factor

Video adapters, keyboard and mouse included

*Monitor sold separately

Specifications

| | | |
|---------------|------------------------------|---|
| SYSTEM | Viewing Streams | Up to 72 |
| | Operating System | Microsoft® Windows 10 Enterprise |
| | Processor | 6th Gen Intel® Core™ i5-6600 |
| | Memory | 8 GB DDR4 RAM |
| | Network Interface | 2 Gigabit Ethernet RJ-45 ports (1000Base-T) |
| | Video Outputs | 2 Active (1 DisplayPort and 1 DVI-I) |
| | Optical Drive | DVD-RW |
| | Supported Monitor Interfaces | Up to 2 combinations of DP, DVI and/or HDMI (with supplied accessories) |

| | | |
|-------------------|--------------------|---|
| MECHANICAL | Form Factor | Desktop |
| | Dimensions (WxHxD) | 175 mm x 360 mm x 435 mm; 6.89" x 14.17" x 17.12" |
| | Weight | 9.24 kg (20.35 lbs) |

| | | |
|-------------------|-------------------|--|
| ELECTRICAL | Power Input | 100 to 240 VAC, 50/60 Hz, auto-switching |
| | Power Supply | Single non-redundant |
| | Power Consumption | 290 W |

| | | |
|----------------------|-----------------------|---|
| ENVIRONMENTAL | Operating Temperature | 5° C to 35° C (41° F to 95° F) |
| | Storage Temperature | -40° C to 65° C (-40° F to 149° F) |
| | Humidity | 20% to 80% relative humidity (non-condensing) |
| | Operating Vibration | 0.26 GRMS |
| | Storage Vibration | 2.20 GRMS |
| | Operating Shock | Shock pulse of 40G for up to 2 ms |
| | Storage Shock | Shock pulse of 105G for up to 2 ms |
| | Storage Altitude | -15.2 m to 10,668 m (-50 ft to 35,000 ft) |

| | |
|-----------------------------|------------------------------|
| SUPPLIED ACCESSORIES | USB Keyboard |
| | USB Mouse |
| | Power cord |
| | 2 DVI to HDMI adapters |
| | 1 DisplayPort to DVI adapter |

| | | | | | |
|-----------------------|---------------------------|------|------|------|------|
| CERTIFICATIONS | Certifications/Directives | UL | cUL | CE | RCM |
| | | CCC | EAC | VCCI | KC |
| | | BSMI | NRCS | RoHS | SVHC |

| | | |
|-----------------------------|--------------|---|
| ORDERING INFORMATION | HD-RMWS3-2MN | Avigilon Control Center Professional high performance remote monitoring workstation for up to 2 monitors* |
| | | * Monitor sold separately |

