

A-3248DZ-EB



Article number: A-3248DZ-EB 1CE
Alternative products: A-3224DZ-EB,
A-3212DZ-EB

A-3248DZ-EB

Specifications

Control keys, buttons and knobs	MIC 1 - 3, MIC 4/AUX 1, AUX 2, MASTER, ON/OFF Zone Selection: 5 zone selector (all zones simultaneously selectable) Bass: ± 10 dB at 100 HZ Treble: ± 10 dB at 10 kHz
Indicator	POWER, SIGNAL, PEAK, PROTECT, Zone Selection 1 - 5 / ALL
Power source.	100 - 240 V AC, 50 / 60 Hz
Audio input	MIC 1 : 1 mV (-60 dBV), 600 Ω , balanced, phone jack, selectable to RJ45, Phantom Power (DC +21V) MIC 2-3 : 1 mV (-60 dBV), 600 Ω , balanced, phone jack MIC 4 : 1 mV (-60 dBV), 600 Ω , balanced, phone jack, selectable to AUX 1 AUX 1 : 100 mV(-20 dBV), 10 k Ω , unbalanced, RCA pin jack, selectable to MIC 4 AUX 2 : 100 mV (-20 dBV), 10 k Ω , unbalanced, RCA pin jack PRIORITY : 0 dBV, 600 Ω , unbalanced removable terminal block
Rated output.	480 W
Audio output	Speaker Out: Speaker output in screw type terminal Direct Line (selectable): 83 Ω (100 V) or 4 Ω Rec Out: 0 dBV, 600 Ω , unbalanced, RCA pin jack
Power source.	100 - 240 V AC, 50 / 60 Hz
Frequency response.	50 Hz - 20 kHz
Control input	Priority Control Input, removable terminal block
Frequency response.	50 Hz - 20 kHz
Power / current consumption	99 W(AC operation at 1/8 maximum output without clip)
Distortion.	< 1 % (at 1 kHz, 1/3 rated output power)
Rated output	480 W
S/N ratio.	60 dB(A) (Over)
Number of channels	5
Connectable microphones	4
Control keys, buttons and knobs	MIC 1 - 3, MIC 4/AUX 1, AUX 2, MASTER, ON/OFF Zone Selection: 5 zone selector (all zones simultaneously selectable) Bass: ± 10 dB at 100 HZ Treble: ± 10 dB at 10 kHz
Inputs	MIC 1 : 1 mV (-60 dBV), 600 Ω , balanced, phone jack, selectable to RJ45 MIC 2-3 : 1 mV (-60 dBV), 600 Ω , balanced, phone jack MIC 4 : 1 mV (-60 dBV), 600 Ω , balanced, phone jack, selectable to AUX 1 AUX 1 : 100 mV(-20 dBV), 10 k Ω , unbalanced, RCA pin jack, selectable to MIC 4 AUX 2 : 100 mV (-20 dBV), 10 k Ω , unbalanced, RCA pin jack PRIORITY : 0 dBV, 600 Ω , unbalanced removable terminal block
Control input	Priority Control Input, removable terminal block
Outputs	Speaker Output : in screw type terminal Direct Line (selectable) : 21 Ω (100V) or 4 Ω Zone Selection : 5 zones simultaneously selectable Rec Out : 0 dB*, 600 Ω , unbalanced, RCA pin jack
Distortion.	< 1 % (at 1 kHz, 1/3 rated output power)
Finish.	ABS resin, Steel plate, black,
Operating temperature.	0°C to +40°C (32°F to 104°F)



A-3248DZ-EB

Appearance