





STRUCTUR

The Structur decorative film allows you to effectively customize your windows and glass partitions. It is decorated with frosted bands of alternating width (35 mm and 5 mm), separated from each other by 5 mm clear aspect bands.



SOLAR SCREEN® Warranty **5 YEARS**



Fire-resistance rating



Storage from -5°C to +40°C





REACH RoHS compliant

RESPECTED

WIDTHS AVAILABLE:



152 cm

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	NC %
Reflection of external visible light	NC %
Reflection of internal visible light	NC %
Total solar energy rejected	%
Total solar energy rejected 2*	%
Solar ratio:	
Solar energy reflection	NC %
Solar energy absorption	NC %
Solar energy transmission	NC %
Reduction in Solar Glare	NC %
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type : Interior	
Roll length	50 m
Film composition	PET
Thickness	$40~\mu$
Colour from the outside: FROSTED	

INSTALLATION ADVICE

Vertical installation and on standard glass surface**


Clear single pane	V
Tinted single pane	~
Reflective tinted single pane	V
Clear double pane	✓
Tinted double pane	V
Reflective tinted double pane	~
Gas-filled double pane - Low E	V
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	V

recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

CONSTRUCTION

- 1. High optical quality polyester with printed design
- 2. PS adhesive, glass polymerization within 15 days
 3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

 $Non-contractual\ data, SOLAR\ SCREEN \&\ reserves\ the\ right\ to\ modify\ the\ composition\ of\ its\ films\ at\ any\ time.\ Consult\ our\ guarantee$ vouchers and our general conditions of sale.