



## ULTIMA 40

Ultima 40 Film is a microperforated adhesive on which a high print quality can be produced. It is suitable for both automotive bodies and glass surfaces. Thanks to its structure, a maximum brightness is maintained (40% VLT). Its white printable side protects you from prying eyes and the black inside allows you to always have a perfect outward view.



SOLAR SCREEN® Warranty  
**2 YEARS**



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

## WIDTHS AVAILABLE:

↔ **152 cm**

## TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	50 %
Visible light transmission	40 %

### FRONT

Technology	Monomeric PVC
Thickness	140 µm
Finish	Micro-perforated warm white

### COMPATIBILITY

Surface(s)	Flat surface
Application type	Outdoor/indoor
Printing method	UV - UV gel - Aqueous print - Latex - Eco solvent - Solvent

### DURABILITY

Outdoor resistance	5 years
Indoor resistance	10 years
Anti-scratch/hard coat	No

### ADHESIVE


Type	Acrylic
Performance	Removable

### LINER

Type	Cardstock
Thickness	160µ

## CONSTRUCTION

1. 100µ monomer PVC
2. Half Permanent Adhesive, allowing the "degassing" of the actual surface, and limits the adhesive transfer during removal
3. Protection release liner, disposable after installation



## MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*